## **Pressure Sensor Fluid PSC-10**

www.bosch-motorsport.com





#### Absolute fluid pressure measurement

- Measurement range 0 to 10 bar
- Analog output

This sensor is designed to measure absolute pressure of various kinds of media e.g. Diesel, gasoline, water, engine oil, transmission oil or air. The sensor is available for two different supply voltage ranges.

The sensor uses stainless steel measuring cells with piezo-resistive measuring bridges in thin layer technique, which are hermetically welded together with stainless steel pressure ports. This guarantees a complete media compatibility.

The main benefit of this sensor is the high quality of a production part at a low price.

| Application             |                                |
|-------------------------|--------------------------------|
| Application             | 0 to 10 bar (a)                |
| Pressure reference type | absolute                       |
| Max. pressure           | 20 bar                         |
| Operating temp. range   | -40 to 125°C                   |
| Media temp. range       | -40 to 125°C                   |
| Storage temp. range     | -20 to 50°C                    |
| Bio fuel compatibility  | E 85 / M 100                   |
| Max. vibration          | 100 m/s² rms at 10 to 2,000 Hz |

#### **Technical Specifications**

#### Variations

|                         | <b>PSC-10</b> (5 V)                        | <b>PSC-10</b> (12 V)          |
|-------------------------|--|-------------------------------|
| Power supply $U_{S}$    | 4.75 to 5.25 V                             | 9 to 30 V                     |
| Full scale output $U_A$ | 10 to 90 % U <sub>s</sub> ratio-<br>metric | 0 to 5 V non-ratio-<br>metric |
| Response time<br>T10/90 | 1.5 ms                                     | 1.0 ms                        |
| Sensitivity             | 400 mV/bar at U <sub>s</sub> =<br>5 V      | 500 mV/bar                    |
| Offset                  | 500 mV at U <sub>s</sub> = 5 V             | 0 mV                          |
| Pin 1                   | -  | Us                            |
| Pin 2                   | Gnd  | Gnd                           |
| Pin 3                   | Sig  | Sig                           |
| Pin 4                   | U <sub>s</sub>                             | -                             |
| Pin 5                   | -  | -                             |
|                         |  |                               |

#### **Mechanical Data**

| Male thread                          | M10x1                                  |
|--------------------------------------|--|
| Wrench size                          | 17 mm                                  |
| Installation torque                  | 15 Nm                                  |
| Weight w/o wire                      | 45 g                                   |
| Sealing                              | O-ring 8.1 x 1.6 mm                    |
| Electrical Data                      |  |
| Power supply $U_{\rm S}$             | Please see variations                  |
| Max power supply $U_s$ max           | ± 30 V                                 |
| Full scale output U <sub>A</sub>     | Please see variations                  |
| Current I <sub>s</sub>               | 8 mA                                   |
| Characteristic                       |  |
| Response time T10/90                 | Please see variations                  |
| Compensated range                    | 0 to 90°C                              |
| Tolerance (FS) at US = 5 V           | ± 0.1 bar                              |
| Tolerance (FS)                       | ±1%                                    |
| Sensitivity                          | Please see variations                  |
| Offset                               | Please see variations                  |
| Connectors and Wires                 |  |
| Connector                            | ASL 6-06-05PC-HE                       |
| Mating connector<br>ASL 0-06-05SC-HE | F 02U 000 228-01                       |
| Sleeve                               | DR-25                                  |
| Wire size                            | AWG 24                                 |
| Wire length L                        | 13 to 95 cm                            |
| Various motorsport and automotiv     | e connectors are available on request. |

Please specify the required wire length with your order.

#### **Installation Notes**

The PSC-10 can be connected directly to most control units.

The sensor has a protection for over voltage, reverse polarity and shortcircuit.

Please do not fix the sensor directly to the engine block to avoid undesired strong vibrations.

Each mounting orientation is possible.

The sensor meets all EMV, EMC and ESD automotive standards.

Please find further application hints in the offer drawing and free download of the sensor configuration file (\*.sdf) for the Bosch Data Logging System at our homepage.

#### Safety Note


The sensor is not intended to be used for safety related applications without appropriate measures for signal validation in the application system.

#### **Ordering Information**

**Pressure Sensor Fluid PSC-10** 4.75 to 5.25 V Order number **F 02U V01 268-01** 

Pressure Sensor Fluid PSC-10 9 to 30 V Order number F 02U V01 295-01

#### Dimensions



#### Represented by:

Europe: Bosch Engineering GmbH Motorsport Robert-Bosch-Allee 1 74232 Abstatt Germany Tel.: +49 7062 911 9101 Fax: +49 7062 911 79104 motorsport@bosch.com www.bosch-motorsport.de

# North America: North America: Bosch Engineering North America Motorsport 38000 Hills Tech Drive Farmington Hills, MI 48331-3417 United States of America Tel.: +1 248 876 2977 Fax: +1 248 876 7373 motorsport@bosch.com www.bosch-motorsport.com

Latin America: Latin America: Robert Bosch Ltda Motorsport Av Juscelino Kubitscheck de Oliveira 11800 Zip code 81460-900 Curitiba - Parana o e u u Brasilia Tel.: +55 41 3341 2057 Fax: +55 41 3341 2779

Asia-Pacific: Asia-Pacific: Bosch Engineering Japan K.K. Motorsport 18F Queen's Tower C, 2:3-5 Minato Mirai Nishi-ku, Yokohama-shi Kanagawa 220-6218 Japan Tel.: +81 45 650 5610 Fax: +81 45 650 5611 www.bosch-motorsport.jp

### Australia, New Zealand and South Africa: Robert Bosch Pty. Ltd Motorsport 1555 Centre Road Clayton, Victoria, 3168 Australia Tel.: +61 (3) 9541 3901 motor.sport@au.bosch.com

© Bosch Engineering GmbH 2017 | Data subject to change without notice 2780256011 | en, V2, 14. Mar 2017